

View Online at <https://aerobasegroup.com/nsn/4720-00-075-4771>

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Tempurature Rating:

-32.0 degrees fahrenheit single response

Outside Diameter:

Between 2.000 inches and 2.062 inches

Quick Disconnect Size:

1.500 inches 2nd end

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Internal quick disconnect 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

400.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, chloroprene and 1st layer braided cotton cord

Maximum Operating Pressure:

100.0 pounds per square inch

Hydrostatic Test Pressure:

200.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and corrosion resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

300.000 inches excluding end fittings

Special Features:

Supplied w/dust cap ms27028-9, dust plug ms27029-9, four gaskets ms27030-5 and four 1-1/2 in. Flat cres hose clamps

Specification Data:

81349-mil-h-11588 government specification

Specification Or Standard:

3 type and 1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0