Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-075-5679

Cross Sectional Snape:         Round         Inside Diameter:         0.750 inches         Bolt Circle Diameter:         2.687 inches 1st end         Charge Thickness:         0.438 inches         0.438 inches         Minimum Inside Bending Radius:         3.750 inches         Flange Outside Diameter:         3.812 inches 1st end         Connection Style:         Plain swivel 1st end         Bolt Hold Diameter:         0.562 inches 1st end         End Connection Design:         Straight 1st end         End Connection Design:         Straight 1st end         Connection Design:         Straight 1st end         End Connection Design:         Straight 1st end         Electrostatic discharge capability and internal support         Layer Composition And Location:         Outer layer braided corresion resistant steel wire         Maximum Operating Pressure:         225.0 pounds per square inch         Hydrostatic Test Pressure:         25.4         Inside Surface Condition:         Convoluted         Measuring Method And Length:         16.000 inches working         Fla	
Inside Diameter:         0.750 inches         Bott Circle Diameter:         2.887 inches 1st end         Flange Thickness:         0.438 inches 1st end         Outside Diameter:         1.093 inches         Minimum Inside Bending Radius:         3.750 inches         Flange Outside Diameter:         3.812 inches 1st end         Connection Style:         Plain swivel 1st end         Doffer Construction:         0.562 inches 1st end         Doffer Construction:         Split 1st end         Connection Design:         Split 1st end         Connection Construction:         Split 1st end         Connection Design:         Split 1st end         Connection Construction:         Plain face flange 1st end         Peatures Provided:         Electrostatic discharge capability and internal support         Lager Composition And Location:         Uoter layer braided corrosion resistant steel wire         Maximum Operating Pressure:         150.0 pounds par square inch         Hydrostatic Test Pressure:         252.0 pounds par square inch         Vacuum In Torr:         25.4	Cross Sectional Shape:
0.750 inches         Bott Circle Diameter:         2.687 inches 1st end         Flange Thickness:         0.438 inches 1st end         Outside Diameter:         1.093 inches         Minimum Inside Bending Radius:         3.750 inches         Flange Outside Diameter:         3.812 inches 1st end         Connection Style:         Pain swivel 1st end         Bott Hole Diameter:         0.662 inches 1st end         Bott Hole Diameter:         0.662 inches 1st end         End Flange Construction:         Split 1st end         End Flange Construction:         Split 1st end         Patrase Rovided:         Patrase Provided:         Electrostatic discharge capability and internal support         Assimum Conscion Top:         Patrase Provided:         150.0 pounds per square inch         Hydrostatic Test Pressure:         150.0 pounds per square inch         Vacuum In Torr:         254         Inside Surface Condition:         Convoluted         Mastring Method And Length:         16.000 inches working         Flange Style:         Roand wib tholes 1st end	
Bolt Circle Diameter:         2.687 inches 1st end         Flange Thickness:         0.438 inches 1st end         Outside Diameter:         1.039 inches         Minimun Inside Bending Radius:         3.750 inches         Flange Outside Diameter:         3.812 inches 1st end         Connection Style:         Plain switch 1st end         Bolt Hole Diameter:         0.662 inches 1st end         Bolt Hole Diameter:         0.562 inches 1st end         End Connection Design:         Straight 1st end         End Connection Design:         Straight 1st end         Connection Design:         Straight 1st end         Pain face flange 1st end         Factures Provided:         Paine face flange 1st end         Factures Provideid corresion resistant steel wire         Maximum Operating Pressure:         120.0 pounds per square inch         Hydrostatic Test Pressure:         225.0 pounds per square inch         Hydrostatic Test Pressure:         25.4         Inside Surface Condition:         Convoluted         Maximum In Torr:         25.4         Inside Surface Condition: </th <th></th>	
2.687 inches 1st end Flange Thickness: 0.438 inches 1st end Outside Diameter: 1.093 inches Minimun Inside Bending Radius: 3.750 inches Flange Outside Diameter: 3.812 inches 1st end Connection Style: Plain swivel 1st end Connection Style: Plain swivel 1st end Contection Design: Contection Design: Straight 1st end Connection Straight 1st end Connection Connection Connection Straight 2st end Connection Connection Connection Straight 2st end Connection	
Flange Thickness:         0.438 linches 1st end         Outside Diameter:         1.038 linches         Minimum Inside Bending Radius:         3.750 linches         Flange Outside Diameter:         3.812 linches 1st end         Connection Style:         Plain swivel 1st end         Bott Hole Diameter:         0.562 linches 1st end         Bott Hole Diameter:         0.562 linches 1st end         End Flange Construction:         Split 1st end         Connection Design:         Straight 1st end         Plantece flange 1st end         Plantece flange 1st end         Features Provided:         Platies end straight 1st end         Connection Type:         Platiace flange 1st end         Features Provided:         Duter layer braided corrosion resistant steel wire         Maximum Operating Pressure:         125.0 pounds per square inch         Hydrostatic Test Pressure:         25.4         Inside Surface Condition:         Convoluted         Measuring Method And Length:         10.000 inches working         Flange Style:         Round w/ both tholes 1st end	
0.438 inches 1st end  Outside Diameter: 1.093 inches  Minimum Inside Bending Radius: 3.750 inches  Flange Outside Diameter: 3.812 inches 1st end Connection Style: Plain swivel 1st end Bott Hole Diameter: 0.562 inches 1st end Edit Hole Diameter: 0.560 inches working Edit Hole Diamete	
Outside Diameter:         1.093 inches         Minimum Inside Bending Radius:         3.750 inches         Flang Outside Diameter:         3.812 inches 1st end         Connection Style:         Plain swivel 1st end         Boit Hole Diameter:         0.562 inches 1st end         End Flange Construction:         Split 1st end         End Flange Construction:         Split 1st end         Connection Design:         Straight 1st end         Connection Type:         Plain swivel 1st end         Connection Type:         Plain face flange 1st end         Features Provided:         Electrostatic discharge capability and internal support         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         15.0 pounds per square inch         Hydrostatic Test Pressure:         25.4         Inside Surface Condition:         Convoluted         Measuring Method And Length:         16.000 inches working         Flange Style:         Round wholt holes 1st end	
1.093 inches         Minimun Inside Bending Radius:         3.750 inches         Flange Outside Diameter:         3.812 inches 1st end         Connection Style:         Plain swivel 1st end         Bott Hole Diameter:         0.562 inches 1st end         End Flange Construction:         Split 1st end         End Flange Construction:         Split 1st end         Connection Design:         Straight 1st end         Pain face flange 1st end         Factures Provided:         Electrostatic discharge capability and internal support         Layer Draided corrosion resistant steel wire         Maximum Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         25.0 pounds per square inch         Vacum In Torr:         25.4         Inice Surface Condition:         Convoluted         Measuring Method And Length:         16.000 inches working         Flange Style:         Round w/ bot holes 1st end	
Minimun Inside Bending Radius:         3.750 inches         Flange Outside Diameter:         3.812 inches 1st end         Connection Style:         Plain swivel 1st end         Bott Hole Diameter:         0.562 inches 1st end         Bott Hole Diameter:         0.562 inches 1st end         End Flange Construction:         Split 1st end         End Connection Design:         Straight 1st end         Connection Type:         Plain face flange 1st end         Fatures Provided:         Course of system of the construction:         Outer layer braided corrosion resistant steel wire         Maximu Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         25.0 pounds per square inch         Hydrostatic Test Pressure:         25.0 pounds per square inch         Hydrostatic Test Pressure:         25.1         Convoluted         Measuring Method And Length:         16.000 inches working         Flange Style:         Round w/ bot holes 1st end	
<ul> <li>3.750 inches</li> <li>Flange Outside Diameter:</li> <li>3.812 inches 1st end</li> <li>Connection Style:</li> <li>Plain swivel 1st end</li> <li>Bott Hole Diameter:</li> <li>0.562 inches 1st end</li> <li>End Flange Construction:</li> <li>Split 1st end</li> <li>End Connection Design:</li> <li>Straight 1st end</li> <li>Connection Type:</li> <li>Plain face flange 1st end</li> <li>Features Provided:</li> <li>Electrostatic discharge capability and internal support</li> <li>Layer Composition And Location:</li> <li>Outer layer braided corrosion resistant steel wire</li> <li>Maximum Operating Pressure:</li> <li>150.0 pounds per square inch</li> <li>Hydrostatic Test Pressure:</li> <li>252.0 pounds per square inch</li> <li>Vacuum In Torr:</li> <li>25.4</li> <li>Inside Surface Condition:</li> <li>Convoluted</li> <li>Flange Style:</li> <li>Nound wb both holes 1st end</li> <li>Staight 51</li> <li>Surfage Style:</li> <li>Round wb both holes 1st end</li> </ul>	
Flange Outside Diameter:         3.812 inches 1st end         Connection Style:         Plain swivel 1st end         Bolt Hole Diameter:         0.562 inches 1st end         End Flange Construction:         Split 1st end         End Connection Design:         Straight 1st end         Connection Type:         Plain face flange 1st end         Features Provided:         Electrostatic discharge capability and internal support         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         150.0 pounds per square inch         Vacurum In Torr:         25.4         Inside Surface Condition:         16.000 inches working         Flange Style:         Noud w bolt holes 1st end	
3.8.2         Increction Style:         Plain swivel 1st end         Bott Hole Diameter:         0.562 inches 1st end         End Flange Construction:         Split 1st end         End Connection Design:         Straight 1st end         Connection Type:         Plain face flange 1st end         Features Provided:         Electrostatic discharge capability and internal support         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         120.0 pounds per square inch         Hydrostatic Test Pressure:         25.4         Inside Surface Condition:         Convoluted         Measuring Method And Length:         16.000 inches working         Flange Style:         Round w/ bott holes 1st end	
Connection Style:Plain swivel 1st endBott Hole Diameter:0.562 inches 1st endEnd Flange Construction:Split 1st endEnd Connection Design:Straight 1st endConnection Type:Plain face flange 1st endFeatures Provided:Electrostatic discharge capability and internal supportLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:25.0 pounds per square inchVacuum In Torr:25.4Inside Surface Condition:ConvolutedMeasuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endShelf Life:	-
Plain swivel 1st end         Bott Hole Diameter:         0.562 inches 1st end         End Flange Construction:         Split 1st end         End Connection Design:         Straight 1st end         Connection Type:         Plain face flange 1st end         Features Provided:         Electrostatic discharge capability and internal support         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         225.0 pounds per square inch         Vacuum In Torr:         25.4         Inside Surface Condition:         16.000 inches working         Flange Style:         Round w/ bolt holes 1st end         Shelf Life:	
Bolt Hole Diameter:0.562 inches 1st endEnd Flange Construction:Split 1st endEnd Connection Design:Straight 1st endConnection Type:Plain face flange 1st endFeatures Provided:Electrostatic discharge capability and internal supportLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:25.4Inside Surface Condition:ConvolutedMesuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endShelf Life:	-
0.562 inches 1st endEnd Flange Construction:Split 1st endEnd Connection Design:Straight 1st endConnection Type:Plain face flange 1st endFeatures Provided:Electrostatic discharge capability and internal supportLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:25.4Inside Surface Condition:ConvolutedMesuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endShelf Life:	
End Flange Construction:Split 1st endEnd Connection Design:Straight 1st endConnection Type:Plain face flange 1st endFeatures Provided:Electrostatic discharge capability and internal supportLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:225.0 pounds per square inchVacuum In Torr:25.4Inside Surface Condition:ConvolutedMeasuring Method And Length:16.00 inches workingFlange Style:Round w bolt holes 1st endShelf Life:	Bolt Hole Diameter:
Split 1st end         End Connection Design:         Straight 1st end         Connection Type:         Plain face flange 1st end         Features Provided:         Electrostatic discharge capability and internal support         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         225.0 pounds per square inch         Vacuum In Torr:         25.4         Inside Surface Condition:         Convoluted         Measuring Method And Length:         16.000 inches working         Flange Style:         Round w/ bolt holes 1st end         Shelf Life:	
Find Connection Design:         Straight 1st end         Connection Type:         Plain face flange 1st end         Features Provided:         Electrostatic discharge capability and internal support         Layer Composition And Location:         Outer layer braided corrosion resistant steel wire         Maximum Operating Pressure:         150.0 pounds per square inch         Hydrostatic Test Pressure:         225.0 pounds per square inch         Vacuum In Torr:         25.4         Inside Surface Condition:         Convoluted         Measuring Method And Length:         16.000 inches working         Flange Style:         Round w/ bolt holes 1st end         Shelf Life:	End Flange Construction:
Straight 1st endConnection Type:Plain face flange 1st endFeatures Provided:Electrostatic discharge capability and internal supportLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:225.0 pounds per square inchVacuum In Torr:25.4Inside Surface Condition:ConvolutedMeasuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endSheff Life:	Split 1st end
Concettion Type:Plain face flange 1st endFeatures Provided:Electrostatic discharge capability and internal supportLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:225.0 pounds per square inchVacuum In Torr:25.4Inside Surface Condition:ConvolutedMeasuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endShelf Life:	End Connection Design:
Plain face flange 1st endFeatures Provided:Electrostatic discharge capability and internal supportLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:225.0 pounds per square inchVacuum In Torr:25.4Inside Surface Condition:ConvolutedMeasuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endShelf Life:	Straight 1st end
Features Provided:Electrostatic discharge capability and internal supportLayer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:225.0 pounds per square inchVacuum In Torr:25.4Inside Surface Condition:ConvolutedMeasuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endShelf Life:	Connection Type:
Electrostatic discharge capability and internal support Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 225.0 pounds per square inch Vacuum In Torr: 25.4 Inside Surface Condition: Convoluted Measuring Method And Length: 16.000 inches working Flange Style: Round w/ bolt holes 1st end Shelf Life:	Plain face flange 1st end
Layer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:225.0 pounds per square inchVacuum In Torr:25.4Inside Surface Condition:ConvolutedMeasuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endSheff Life:	Features Provided:
Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:225.0 pounds per square inchVacuum In Torr:25.4Inside Surface Condition:ConvolutedMeasuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endShelf Life:	Electrostatic discharge capability and internal support
Maximum Operating Pressure:150.0 pounds per square inchHydrostatic Test Pressure:225.0 pounds per square inchVacuum In Torr:25.4Inside Surface Condition:ConvolutedMeasuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endShelf Life:	Layer Composition And Location:
<ul> <li>150.0 pounds per square inch</li> <li>Hydrostatic Test Pressure:</li> <li>225.0 pounds per square inch</li> <li>Vacuum In Torr:</li> <li>25.4</li> <li>Inside Surface Condition:</li> <li>Convoluted</li> <li>Measuring Method And Length:</li> <li>16.000 inches working</li> <li>Flange Style:</li> <li>Round w/ bolt holes 1st end</li> <li>Shelf Life:</li> </ul>	Outer layer braided corrosion resistant steel wire
Hydrostatic Test Pressure:225.0 pounds per square inchVacuum In Torr:25.4Inside Surface Condition:ConvolutedMeasuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endShelf Life:	Maximum Operating Pressure:
225.0 pounds per square inch Vacuum In Torr: 25.4 Inside Surface Condition: Convoluted Measuring Method And Length: 16.000 inches working Flange Style: Round w/ bolt holes 1st end Shelf Life:	
Vacuum In Torr: 25.4 Inside Surface Condition: Convoluted Measuring Method And Length: 16.000 inches working Flange Style: Round w/ bolt holes 1st end Shelf Life:	Hydrostatic Test Pressure:
25.4 Inside Surface Condition: Convoluted Measuring Method And Length: 16.000 inches working Flange Style: Round w/ bolt holes 1st end Shelf Life:	225.0 pounds per square inch
Inside Surface Condition:ConvolutedMeasuring Method And Length:16.000 inches workingFlange Style:Round w/ bolt holes 1st endShelf Life:	
Convoluted Measuring Method And Length: 16.000 inches working Flange Style: Round w/ bolt holes 1st end Shelf Life:	
Measuring Method And Length: 16.000 inches working Flange Style: Round w/ bolt holes 1st end Shelf Life:	Inside Surface Condition:
16.000 inches working Flange Style: Round w/ bolt holes 1st end Shelf Life:	Convoluted
Flange Style: Round w/ bolt holes 1st end Shelf Life:	Measuring Method And Length:
Round w/ bolt holes 1st end Shelf Life:	16.000 inches working
Shelf Life:	Flange Style:
	Round w/ bolt holes 1st end
N/a	Shelf Life:
	N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0