NSN 4720-00-075-5680

Nonmetallic Hose Assembly - Page 1 of 2



Tremmetame Floor Accessory Trage For E
View Online at https://aerobasegroup.com/nsn/4720-00-075-5680
Cross Sectional Shape:
Round
Inside Diameter:
0.750 inches
Bolt Circle Diameter:
2.687 inches 1st end
Flange Thickness:
0.500 inches 1st end
Outside Diameter:
1.093 inches
Minimum Inside Bending Radius:
3.750 inches
Flange Outside Diameter:
3.812 inches 1st end
Connection Style:
Raised swivel 1st end
Bolt Hole Diameter:
0.562 inches 1st end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
1.750 inches 1st end
End Flange Construction:
Split 1st end
End Connection Design:
Straight 1st end
Connection Type:
Raised face flange 1st end
Features Provided:
Electrostatic discharge capability and internal support
Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

150.0 pounds per square inch

Hydrostatic Test Pressure:

225.0 pounds per square inch

Vacuum In Torr:

25.4

Inside Surface Condition:

Convoluted

Measuring Method And Length:

16.000 inches working

NSN 4720-00-075-5680

Nonmetallic Hose Assembly - Page 2 of 2



FI	an	ge	Sty	le:

Round w/ bolt holes 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0