Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-076-9985

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.344 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 375.0 degrees fahrenheit single response
Outside Diameter:
0.547 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.500 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
63.500 inches
Special Features:
Three bolt hole flange on both ends
Media For Which Designed:
Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0