

View Online at <https://aerobasegroup.com/nsn/4720-00-077-1615>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.485 inches and 0.531 inches

**Temperature Rating:**

-67.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.875 inches and 0.937 inches

**Minimum Inside Bending Radius:**

7.000 inches

**End Application:**

30a armored vehicle launch bridge (avlb), m60a1 and m48a5; tank, m-60 series

**Connection Style:**

Swivel nut with compression sleeve 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

16 1st end

**Burst Test Pressure:**

8000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and outer layer molded rubber, chloroprene

**Maximum Operating Pressure:**

2000.0 pounds per square inch

**Thread Size:**

0.938 inches 1st end

**Hydrostatic Test Pressure:**

4000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Mildew resistant and oil resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

28.000 inches

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0