NSN 4720-00-078-2512

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-078-2512

Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.810 inches
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided corrosion resistant steel wire
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
37.0 degrees 1st end Outer Covering Environmental Protection:
Outer Covering Environmental Protection:
Outer Covering Environmental Protection: Abrasion resistant and oil resistant and waterproof
Outer Covering Environmental Protection: Abrasion resistant and oil resistant and waterproof Inside Surface Condition:
Outer Covering Environmental Protection: Abrasion resistant and oil resistant and waterproof Inside Surface Condition: Smooth

Unf 1st end

Thread Series Designator:

Hydraulic fluid and fuel/oil, hydrocarbon single response

NSN 4720-00-078-2512

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0