## NSN 4720-00-078-8689

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-078-8689

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.875 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.156 inches
Minimum Inside Bending Radius:
5.500 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage
Maximum Operating Pressure:
750.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1500.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:

## NSN 4720-00-078-8689

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Me	ethod And Length
18.250 inches	working

Media For Which Designed:
Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 1st end

**Specification Data:** 

81349-mil-h-83797 government specification

**Specification Or Standard:** 

16 size

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

Yes - demil/mli

Fiig:

A542a0