NSN 4720-00-079-0059

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-079-0059

-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response						
Outside Diameter:						
0.312 inches						
Minimum Inside Bending Radius:						
2.000 inches						
Exterior Color:						
Natural						
Connection Style:						
Swivel nut flare 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Burst Test Pressure:						
12000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided corrosion resistant steel wire						
Maximum Operating Pressure:						
1500.0 pounds per square inch						
Thread Size:						
0.438 inches 1st end						
Seat Angle:						
37.0 degrees 2nd end						
Hydrostatic Test Pressure:						
3000.0 pounds per square inch						
Flow Angle:						
90.0 degrees 2nd end						
Outer Covering Environmental Protection:						
Corrosion resistant						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
118.800 inches working and 121.200 inches working						

NSN 4720-00-079-0059

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ed

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0