NSN 4720-00-079-6010

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-079-6010

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Inner Conveying Tube Style:
Interlocked unpacked
Exterior Color:
Natural
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Features Provided:
Identical ends
Burst Test Pressure:
Burst Test Pressure: 12000.0 pounds per square inch
12000.0 pounds per square inch
12000.0 pounds per square inch Layer Composition And Location:
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size:
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.500 inches 1st end
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure:
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection:
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length:
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length: 13.500 inches
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length: 13.500 inches Thread Series Designator:
12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.500 inches 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Outer Covering Environmental Protection: Corrosion resistant Measuring Method And Length: 13.500 inches Thread Series Designator: Npt 1st end

NSN 4720-00-079-6010

Metallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0