NSN 4720-00-079-8166

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-079-8166

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 2a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.125 inches |
| Tempurature Rating: |
| -55.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.480 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut, inverted flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external tube 1st end |
| Burst Test Pressure: |
| 5000.0 pounds per square inch |
| Layer Composition And Location: |
| 2nd layer braided cotton cord and outer layer molded rubber, synthetic and 1st layer braided cotton cord |
| Thread Size: |
| 0.375 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Weatherproof |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 16.750 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4720-00-079-8166

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0