Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-080-3870

Cross Sectional Shape: Round Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.188 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.469 inches Minimun Inside Bending Radius: 3.500 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type: Threaded internal tube 1st end
Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.188 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.469 inches Minimum Inside Bending Radius: 3.500 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.188 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.469 inches 0.469 inches Minimum Inside Bending Radius: 3.500 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
Thread Direction: Right-hand 1st end Inside Diameter: 0.188 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.469 inches Minimum Inside Bending Radius: 3.500 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
Right-hand 1st endInside Diameter:0.188 inchesTempurature Rating:-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single responseOutside Diameter:0.469 inchesMinimum Inside Bending Radius:3.500 inchesExterior Color:BlackConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 2nd endConnection Type:
Inside Diameter: 0.188 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.469 inches Minimum Inside Bending Radius: 3.500 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
0.188 inches Tempurature Rating: -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.469 inches Minimum Inside Bending Radius: 3.500 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
Tempurature Rating:-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single responseOutside Diameter:0.469 inchesMinimum Inside Bending Radius:3.500 inchesExterior Color:BlackConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 2nd endConnection Type:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response Outside Diameter: 0.469 inches Minimum Inside Bending Radius: 3.500 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
Outside Diameter:0.469 inchesMinimum Inside Bending Radius:3.500 inchesExterior Color:BlackConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 2nd endConnection Type:
0.469 inches Minimum Inside Bending Radius: 3.500 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
Minimum Inside Bending Radius: 3.500 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
3.500 inchesExterior Color:BlackConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 2nd endConnection Type:
Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
Swivel nut flare 1st end End Connection Design: Straight 2nd end Connection Type:
End Connection Design: Straight 2nd end Connection Type:
Straight 2nd end Connection Type:
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nonskive
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Vacuum In Torr:
50.8
Inside Surface Condition:



Measuring Method And Length:

16.000 inches working

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0