Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-080-6333

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.625 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Outside Diameter:	
0.969 inches	
Minimum Inside Bending Radius:	
2.750 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Thready Qty Per Inch (tpi):	
14 1st end	
Burst Test Pressure:	
3000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided t	extile yarn
Maximum Operating Pressure:	
750.0 pounds per square inch	
Thread Size:	
1.062 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
15000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Cold resistant and mildew resistant and oil resistant	
Inside Surface Condition:	
Smooth	

Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 42.250 inches Media For Which Designed: Air and fuel/oil, hydrocarbon and water single response Thread Series Designator: Uns 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization:

No

Fiig:

A542a0