NSN 4720-00-080-6340

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-080-6340 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.875 inches **Minimum Inside Bending Radius:** 5.500 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 7000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided wire and outer layer rubber impregnated braided cotton cord and 1st layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 1750.0 pounds per square inch **Thread Size:** 0.875 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 3500.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:**

30.000 inches

Media For Which Designed:

Air single response

NSN 4720-00-080-6340

Nonmetallic Hose Assembly - Page 2 of 2



| T1 | 0! | D! | |
|--------|--------|--------|-------|
| Thread | Series | Design | ator: |

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0