Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-080-6597

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.125 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.480 inches
Minimum Inside Bending Radius:
4.500 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Socket rubber synthetic all ends
Fitting Component And Surface Treatment:
Complete fitting cadmium 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Not identical Burst Test Pressure:
1000.0 pounds per square inch
First End Swivel Action Capability: Not included
Layer Composition And Location:
Outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch Thread Size:
1.625 inches 1st end



Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 500.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length: 24.625 inches excluding end fittings Second End Swivel Action Capability: Not included **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Un 1st end Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A542a0