

View Online at <https://aerobasegroup.com/nsn/4720-00-080-8586>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.500 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.781 inches

**Minimum Inside Bending Radius:**

3.750 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Burst Test Pressure:**

750.0 pounds per square inch

**Layer Composition And Location:**

Outer layer molded rubber, synthetic and 1st layer braided textile yarn

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

45.0 degrees 1st end

**Hydrostatic Test Pressure:**

375.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and mildew resistant and oil resistant and ozone resistant

**Vacuum In Torr:**

254.0

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

216.000 inches

**Media For Which Designed:**

Hydraulic fluid single response

**Thread Series Designator:**

Unf 1st end

**Specification Data:**

81349-mil-h-13444 government specification

**Specification Or Standard:**

1 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0

**Mil-std (military Standard):**

Mil-h-13444 spec.