

View Online at <https://aerobasegroup.com/nsn/4720-00-083-0047>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

4.000 inches

**Temperature Rating:**

-25.0 degrees fahrenheit and 100.0 degrees fahrenheit single response

**Outside Diameter:**

4.500 inches

**Quick Disconnect Size:**

4.000 inches 2nd end

**Connection Style:**

Cam or lever (external) 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Internal quick disconnect 1st end

**Burst Test Pressure:**

600.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided cotton cord and outer layer molded rubber, chloroprene and 1st layer braided cotton cord

**Maximum Operating Pressure:**

125.0 pounds per square inch

**Hydrostatic Test Pressure:**

250.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant and fuel resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

25.0 feet excluding end fittings

**Special Features:**

End fittings to be furnished completely assembled with aa59326ix19 dust cap, aa59326x19 dust plug, two 121 a-a-59326 gasket, and four /4/ hose clamps

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Specification Data:**

81349-mil-prf-11588 government specification

**Specification Or Standard:**

1 class and 3 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-prf-11588 spec.