Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-083-0048

Cross Sectional Shape:

Round

Inside Diameter:

3.000 inches

Tempurature Rating:

25.0 degrees fahrenheit and 125.0 degrees fahrenheit single response

Outside Diameter:

Between 3.188 inches and 3.625 inches

Quick Disconnect Size:

3.000 inches 2nd end

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Internal quick disconnect 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

500.0 pounds per square inch

Layer Composition And Location:

2nd layer braided cotton cord and outer layer molded rubber, chloroprene and 1st layer braided cotton cord

Maximum Operating Pressure:

125.0 pounds per square inch

Hydrostatic Test Pressure:

250.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and corrosion resistant and acid resistant and fuel resistant and hydraulic solution resistant and oil resistant and ozone

resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

50.0 feet excluding end fittings

Special Markings:

Hose, liquid petroleum fuels, dispensing, collapsible type 3, 500 p.S.I.G. burst

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Specification Data:

81349-prf11588 government specification

Specification Or Standard:

3 type and 1 class and 3-inch size

Shelf Life:

N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-11588 spec.