## NSN 4720-00-084-3632

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-084-3632

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber and 1st layer braided cotton cord
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant
Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
Measuring Method And Length:

12.000 inches working

## NSN 4720-00-084-3632

Nonmetallic Hose Assembly - Page 2 of 2



	Media	For	Which	Design	ned:
--	-------	-----	-------	--------	------

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unjf 1st end

**Specification Data:** 

88044-an6270 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0