## NSN 4720-00-085-1040



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-085-1040 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 180.0 degrees fahrenheit single response **Outside Diameter:** 0.500 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 800.0 pounds per square inch **Layer Composition And Location:** Outer layer molded plastic and 1st layer braided cotton cord **Maximum Operating Pressure:** 200.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 400.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 

18.250 inches working

Thread Series Designator:
Unf 1st end

Specification Data:
88044-an6270 government standard

Shelf Life:
N/a

Unit Of Measure:
--

## NSN 4720-00-085-1040

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0