NSN 4720-00-086-5762

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-086-5762 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.438 inches **Tempurature Rating:** -67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 1.110 inches **Minimum Inside Bending Radius:** 7.000 inches **Exterior Color:** Natural **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** 2nd layer molded rubber, synthetic and outer layer spirally laid corrosion resistant steel wire and 1st layer braided steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 12.0 degrees 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Outer Covering Environmental Protection:** Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

216.000 inches

NSN 4720-00-086-5762

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
----------------	-----------

W/synthetic rubber chafe guard

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0