NSN 4720-00-087-4665

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-087-4665 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.781 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 18 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber and 1st layer braided steel wire **Maximum Operating Pressure:** 2250.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 4500.0 pounds per square inch **Outer Covering Environmental Protection:** Mildew resistant and oil resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 35.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

NSN 4720-00-087-4665

Nonmetallic Hose Assembly - Page 2 of 2



_				
٧n	ACIT	I へっti	An I	Data:
บม	CUII	ıvaıı	UII I	vala.

81349-mil-h-13531 government specification

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0