Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-087-6922

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
Between 0.492 inches and 0.523 inches	
Outside Diameter:	
Between 0.891 inches and 0.953 inches	
Connection Style:	
Plain 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Thready Qty Per Inch (tpi):	
14 1st end	
Burst Test Pressure:	
7000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord	
Maximum Operating Pressure:	
1750.0 pounds per square inch	
Thread Size:	
0.500 inches 1st end	
Seat Angle:	
90.0 degrees 1st end	
Hydrostatic Test Pressure:	
3500.0 pounds per square inch	
Outer Covering Environmental Protection:	
Mildew resistant and oil resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
18.880 inches working and 19.120 inches working	
Media For Which Designed:	
Air single response	
Thread Series Designator:	
Nptf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 4720-00-087-6922

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0