Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-087-8583

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Natural
Angle Between Rigid Elbow Fittings In Deg:
10.0
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
50.8

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:

Smooth

Measuring Method And Length:

29.000 inches working

Media For Which Designed:

Air single response and alcohol, ethyl single response and alcohol, methyl single response and fuel/oil, hydrocarbon single response and water, fresh single response and water, salt single response

Thread Series Designator:

Unf 1st end

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.