Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-087-9327

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.875 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
12 2nd end	
Burst Test Pressure:	
3200.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and	1st layer braided cotton cord
Maximum Operating Pressure:	
800.0 pounds per square inch	
Thread Size:	
0.625 inches 2nd end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure:	
1600.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
5.500 inches excluding end fittings	
Thread Series Designator:	
Unf 2nd end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

NSN 4720-00-087-9327

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

