

View Online at <https://aerobasegroup.com/nsn/4720-00-088-0224>

Cross Sectional Shape:

Round

Inside Diameter:

1.125 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Bolt Circle Diameter:

2.312 inches 1st end

Flange Thickness:

0.531 inches 2nd end

Outside Diameter:

1.500 inches

Minimum Inside Bending Radius:

9.000 inches

Center To Center Distance Between Bolt Holes Along Width:

2.000 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.000 inches 2nd end

Bolt Hole Quantity:

3 1st end

Flange Length:

2.500 inches 1st end

Flange Width:

2.500 inches 1st end

Connection Style:

Plain 2nd end

Bolt Hole Diameter:

0.344 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Burst Test Pressure:

2500.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord

Maximum Operating Pressure:

600.0 pounds per square inch

Hydrostatic Test Pressure:

1250.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

35.000 inches

Flange Style:

Triangular 1st end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0