

View Online at <https://aerobasegroup.com/nsn/4720-00-088-5543>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

-100.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Flange Thickness:

0.234 inches 2nd end

Outside Diameter:

1.109 inches

Minimum Inside Bending Radius:

7.375 inches

Angle Between Rigid Elbow Fittings In Deg:

230.0

Center To Center Distance Between Bolt Holes Along Width:

1.312 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.312 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

1.750 inches 2nd end

Flange Width:

1.750 inches 2nd end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.205 inches 2nd end

Raised Face Height:

0.030 inches 2nd end

Raised Face Diameter:

1.510 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

1.312 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Vacuum In Torr:

406.4

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.000 inches working

Flange Style:

Rectangular (includes square) 2nd end

Thread Series Designator:

Unj 1st end

Specification Data:

81349-mil-h-25579 government specification

Specification Or Standard:

1 class and 16z size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.