Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-088-5685

Cross \$	Sectional Shape:
Round	
Thread	Class:
3b 1st e	end
Thread	Direction:
Right-ha	and 1st end
Inside I	Diameter:
0.485 ir	nches
Tempu	rature Rating:
-65.0 de	egrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside	e Diameter:
1.015 ir	nches
Minimu	ım Inside Bending Radius:
3.250 ir	nches
Connec	ction Style:
Swivel r	nut flare 1st end
End Co	onnection Design:
Straight	t 1st end
Connec	ction Type:
Threade	ed internal tube 1st end
Feature	es Provided:
Electros	static discharge capability
Burst T	est Pressure:
12000.0	) pounds per square inch
Layer C	Composition And Location:
Outer la	ayer braided corrosion resistant steel wire
Maxim	um Operating Pressure:
3000.0	pounds per square inch
Thread	Size:
0.875 ir	nches 1st end
Seat Ar	ngle:
37.0 de	grees 1st end
Hydros	static Test Pressure:
6000.0	pounds per square inch
Outer C	Covering Environmental Protection:
Corrosi	on resistant
Inside \$	Surface Condition:
Smooth	1
Measur	ring Method And Length:
18.500	inches
Thread	Series Designator:
Unjf 1st	end

Nonmetallic Hose Assembly - Page 2 of 2



**Specification Data:** 

81343-as153 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

## Mil-std (military Standard):

Mil-h-38360 spec.