

View Online at <https://aerobasegroup.com/nsn/4720-00-089-0259>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.250 inches and 0.281 inches

Temperature Rating:

0.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.563 inches and 0.625 inches

Minimum Inside Bending Radius:

3.000 inches

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

800.0 pounds per square inch

Layer Composition And Location:

Outer layer rubber impregnated polyamide fabric

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

0.250 inches 2nd end

Hydrostatic Test Pressure:

400.0 pounds per square inch

Outer Covering Environmental Protection:

Ozone resistant and mildew resistant

Inside Surface Condition:

Smooth

Media For Which Designed:

Water single response

Thread Series Designator:

Npt 1st end

Reference Number Differentiating Characteristics:

As differentiated by inner conveying surface material, covering materials, and burst pressure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0