

View Online at <https://aerobasegroup.com/nsn/4720-00-090-6389>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.406 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Flange Thickness:

0.234 inches 2nd end

Outside Diameter:

0.562 inches

Minimum Inside Bending Radius:

4.620 inches

Center To Center Distance Between Bolt Holes Along Width:

0.950 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

0.950 inches 2nd end

Bolt Hole Quantity:

4 1st end

Flange Length:

1.390 inches 2nd end

Flange Width:

1.390 inches 2nd end

Connection Style:

Raised swivel 2nd end

Bolt Hole Diameter:

0.205 inches 2nd end

Raised Face Height:

0.020 inches 2nd end

Raised Face Diameter:

0.875 inches 2nd end

End Flange Construction:

Split 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.500 inches working

Flange Style:

Rectangular (includes square) 2nd end

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0