Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-092-9266

Cross Sectional Shape: Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Outside Diameter:** 0.594 inches **Unable To Decode:** Unable to decode or unable to decode **Exterior Color:** Black Hose Or Tubing Specification/std Data: Zz-h-461 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Connection Style:** Plain 2nd end **End Connection Design:** Straight 2nd end **End Fitting Component And Material:** Complete fitting copper alloy all ends **Connection Type:** Threaded internal boss 1st end Second End Relationship With First End: Not identical **Burst Test Pressure:** 700.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: Outer layer molded rubber Maximum Operating Pressure: 150.0 pounds per square inch **Thread Size:** 0.500 inches 1st end **Hydrostatic Test Pressure:** 250.0 pounds per square inch **Inside Surface Condition:** Smooth Measuring Method And Length:

720.000 inches excluding end fittings

Nonmetallic Hose Assembly - Page 2 of 2



Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, natural or rubber, synthetic

Media For Which Designed:

Air single response

Thread Series Designator:

Unf 1st end

Specification Data:

Zz-h-461 professional/industrial association specification

Specification Or Standard:

A style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0