NSN 4720-00-093-1512

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-093-1512 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.750 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 1.030 inches **Minimum Inside Bending Radius:** 7.000 inches **Connection Style:** Plain 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided textile yarn **Maximum Operating Pressure:** 250.0 pounds per square inch **Thread Size:** 0.750 inches 1st end **Hydrostatic Test Pressure:** 500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 144.000 inches Media For Which Designed: Fuel/oil, hydrocarbon and water and hydraulic fluid, water base and air single response **Thread Series Designator:** Nptf 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 4720-00-093-1512

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0