

View Online at <https://aerobasegroup.com/nsn/4720-00-095-4695>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.422 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

**Outside Diameter:**

0.815 inches

**Minimum Inside Bending Radius:**

8.000 inches

**Exterior Color:**

Natural

**Connection Style:**

Swivel nut with loose or integral clinch sleeve 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

22000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer spirally wrapped corrosion resistant steel fabric and outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

5500.0 pounds per square inch

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

11000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant

**Criticality Code Justification:**

Zzzy

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

18.500 inches working

**Special Features:**

Each hose assembly packaged in a heat-sealed polyethylene tube

**Thread Series Designator:**

Unjf 1st end

**Reference Number Differentiating Characteristics:**

Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0