NSN 4720-00-096-9060

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-096-9060

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Flange Thickness:
0.317 inches 2nd end
Outside Diameter:
1.560 inches
Minimum Inside Bending Radius:
12.000 inches
Flange Outside Diameter:
1.750 inches 2nd end
Connection Style:
Plain w/ gasket groove (sae flanged head) 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided wire and 3rd layer molded rubber, synthetic and 1st layer molded rubber, synthetic
Maximum Operating Pressure:
2500.0 pounds per square inch
Thread Size:
1.000 inches 1st end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
30.500 inches
Flange Style:
Round w/ out bolt holes 2nd end
Media For Which Designed:

Hydraulic fluid single response

NSN 4720-00-096-9060

Nonmetallic Hose Assembly - Page 2 of 2



Th	ıre	ea	d	Series	Designator:
				_	

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0