

View Online at <https://aerobasegroup.com/nsn/4720-00-101-3707>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.719 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Connection Style:**

Swivel nut, gasket seal 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal pipe 1st end

**Burst Test Pressure:**

1200.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided rayon cord and outer layer molded rubber, chloroprene and 1st layer braided rayon cord

**Maximum Operating Pressure:**

300.0 pounds per square inch

**Thread Size:**

0.250 inches 2nd end

**Seat Angle:**

30.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Abrasion resistant and ozone resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

15.000 inches

**Special Features:**

Barbed insert type fittings first end and swivel female ball end style fittings

**Media For Which Designed:**

Air and fuel/oil, hydrocarbon and paint and water single response

**Thread Series Designator:**

Nptf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0