

View Online at <https://aerobasegroup.com/nsn/4720-00-101-3707>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.719 inches

Minimum Inside Bending Radius:

4.000 inches

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal pipe 1st end

Burst Test Pressure:

1200.0 pounds per square inch

Layer Composition And Location:

2nd layer braided rayon cord and outer layer molded rubber, chloroprene and 1st layer braided rayon cord

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.250 inches 2nd end

Seat Angle:

30.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and ozone resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.000 inches

Special Features:

Barbed insert type fittings first end and swivel female ball end style fittings

Media For Which Designed:

Air and fuel/oil, hydrocarbon and paint and water single response

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0