Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-101-7615

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 2b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.375 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.688 inches  |
| Minimum Inside Bending Radius:  |
| 5.000 inches  |
| Exterior Color:   |
| Black   |
| Angle Between Rigid Elbow Fittings In Deg:                            |
| 270.0   |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Elbow 1st end   |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 9000.0 pounds per square inch   |
| Layer Composition And Location:                                       |
| Outer layer molded rubber, synthetic and 1st layer braided wire       |
| Maximum Operating Pressure:   |
| 2250.0 pounds per square inch   |
| Thread Size:  |
| 0.562 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 4500.0 pounds per square inch   |
| Flow Angle:   |
| 90.0 degrees 1st end  |
| Outer Covering Environmental Protection:                              |
| Oil resistant and weatherproof  |
| Inside Surface Condition:   |
| Smooth  |
|   |

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 27.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: --

No

Fiig:

A542a0