## NSN 4720-00-103-2460

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-103-2460

Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.375 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response				
Outside Diameter:				
0.680 inches				
Minimum Inside Bending Radius:				
5.000 inches				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
9000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer molded rubber, synthetic and 1st layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
2250.0 pounds per square inch				
Thread Size:				
0.562 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
4500.0 pounds per square inch				
Outer Covering Environmental Protection:				
Oil resistant and ozone resistant and weatherproof				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
16.000 inches excluding end fittings				

Unjf 1st end

Media For Which Designed:

**Thread Series Designator:** 

Fuel/oil, hydrocarbon single response

## NSN 4720-00-103-2460

Nonmetallic Hose Assembly - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0