

View Online at <https://aerobasegroup.com/nsn/4720-00-103-3557>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.125 inches

**Temperature Rating:**

600.0 degrees fahrenheit single response

**Bolt Circle Diameter:**

1.656 inches 2nd end

**Flange Thickness:**

0.234 inches 2nd end

**Outside Diameter:**

1.344 inches

**Recess Diameter:**

1.844 inches 2nd end

**Recess Depth:**

0.136 inches 2nd end

**Minimum Inside Bending Radius:**

9.000 inches

**Exterior Color:**

Black

**Angle Between Rigid Elbow Fittings In Deg:**

270.0

**Bolt Hole Quantity:**

4 2nd end

**Flange Outside Diameter:**

2.875 inches 2nd end

**Connection Style:**

Swivel nut flare 1st end

**Bolt Hole Diameter:**

0.266 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

4000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Thread Size:**

1.625 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Flow Angle:**

90.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

23.875 inches working

**Flange Style:**

Round w/ bolt holes 2nd end

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A542a0