

View Online at <https://aerobasegroup.com/nsn/4720-00-103-3557>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.125 inches

Temperature Rating:

600.0 degrees fahrenheit single response

Bolt Circle Diameter:

1.656 inches 2nd end

Flange Thickness:

0.234 inches 2nd end

Outside Diameter:

1.344 inches

Recess Diameter:

1.844 inches 2nd end

Recess Depth:

0.136 inches 2nd end

Minimum Inside Bending Radius:

9.000 inches

Exterior Color:

Black

Angle Between Rigid Elbow Fittings In Deg:

270.0

Bolt Hole Quantity:

4 2nd end

Flange Outside Diameter:

2.875 inches 2nd end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.266 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

1.625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

23.875 inches working

Flange Style:

Round w/ bolt holes 2nd end

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0