Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-103-5530

| Cross Sectional Shape: |
|--|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.312 inches |
| Tempurature Rating: |
| -67.0 degrees fahrenheit and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| Between 0.515 inches and 0.547 inches |
| Minimum Inside Bending Radius: |
| 2.750 inches |
| Connection Style: |
| Plain 2nd end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded external pipe 2nd end |
| Burst Test Pressure: |
| 1100.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer molded rubber, synthetic and 1st layer braided fabric |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch |
| Thread Size: |
| 0.250 inches 1st end |
| Hydrostatic Test Pressure: |
| 550.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Fuel resistant and mildew resistant and oil resistant and ozone resistant and waterproof |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 28.000 inches |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Npt 1st end |
| Specification Data: |
| 81349-mil-h-13444 government specification |
| Specification Or Standard: |
| 1 type |
| |

NSN 4720-00-103-5530

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13444 spec.

