NSN 4720-00-103-5530

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-103-5530

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
Between 0.515 inches and 0.547 inches
Minimum Inside Bending Radius:
2.750 inches
Connection Style:
Plain 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external pipe 2nd end
Burst Test Pressure:
1100.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided fabric
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Hydrostatic Test Pressure:
550.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and mildew resistant and oil resistant and ozone resistant and waterproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
28.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Npt 1st end
Specification Data:
81349-mil-h-13444 government specification
Specification Or Standard:
1 type

NSN 4720-00-103-5530

Nonmetallic Hose Assembly - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A542a0	

Mil-std (military Standard):

Mil-h-13444 spec.

Shelf Life: