## NSN 4720-00-103-5641



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-103-5641 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.690 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings **Burst Test Pressure:** 20000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and outer layer molded rubber, synthetic and 1st layer braided steel wire **Maximum Operating Pressure:** 5000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 10000.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Oil resistant and weatherproof

**Inside Surface Condition:** 

**Measuring Method And Length:** 

19.500 inches

Smooth

## NSN 4720-00-103-5641

Nonmetallic Hose Assembly - Page 2 of 2



| Media | For | Which | Design | ed |
|-------|-----|-------|--------|----|
|       |     |       |        |    |

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0