NSN 4720-00-103-8317

Metallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-103-8317

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Outside Diameter:
0.922 inches
Minimum Inside Bending Radius:
6.500 inches
Inner Conveying Tube Style:
Annular close-pitch corrugated
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Features Provided:
Identical ends
Burst Test Pressure:
Burst Test Pressure: 3000.0 pounds per square inch
3000.0 pounds per square inch
3000.0 pounds per square inch Layer Composition And Location:
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure:
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch Thread Size:
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch Thread Size: 0.500 inches 1st end
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length:
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 12.000 inches
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 12.000 inches Thread Series Designator:
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 12.000 inches Thread Series Designator: Npt 1st end
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 12.000 inches Thread Series Designator: Npt 1st end Shelf Life:
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 12.000 inches Thread Series Designator: Npt 1st end Shelf Life: N/a
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 12.000 inches Thread Series Designator: Npt 1st end Shelf Life: N/a
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 12.000 inches Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure:
3000.0 pounds per square inch Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 700.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 12.000 inches Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: