

View Online at <https://aerobasegroup.com/nsn/4720-00-104-1965>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit and 158.0 degrees fahrenheit single response

Outside Diameter:

0.438 inches

Minimum Inside Bending Radius:

2.000 inches

Hose Or Tubing Specification/std Data:

Mil mil-h-5593, size no. 3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Mil mil-a-38726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting aluminum alloy all ends

Fitting Component And Surface Treatment:

Complete fitting anodize 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Second End Relationship With First End:

Identical

Burst Test Pressure:

1700.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

Outer layer molded rubber, synthetic

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and water resistant

Vacuum In Torr:

254.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

6.375 inches working

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Data:

88044-an6270 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0