

View Online at <https://aerobasegroup.com/nsn/4720-00-104-9039>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.412 inches and 0.462 inches

**Outside Diameter:**

Between 0.785 inches and 0.815 inches

**Minimum Inside Bending Radius:**

8.000 inches

**Exterior Color:**

Gray

**Connection Style:**

Inverted flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

22000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer spirally laid corrosion resistant steel wire and outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

6000.0 pounds per square inch

**Thread Size:**

1.750 inches 1st end

**Seat Angle:**

37.5 degrees 1st end

**Hydrostatic Test Pressure:**

12000.0 pounds per square inch

**Criticality Code Justification:**

Zzzy

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

16.500 inches

**Thread Series Designator:**

Unf 1st end

**Reference Number Differentiating Characteristics:**

Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A542a0