NSN 4720-00-107-1208

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-107-1208 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.875 inches **Minimum Inside Bending Radius:** 7.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 14000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided wire and outer layer molded rubber, synthetic and 1st layer braided wire **Maximum Operating Pressure:** 3500.0 pounds per square inch **Thread Size:** 0.875 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 7000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 62.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end

Shelf Life:

N/a

NSN 4720-00-107-1208

Nonmetallic Hose Assembly - Page 2 of 2



		• .					
	In	iŧ	Of	MAG	200		ω.
•	,,,	ıL	v.	IAIC	as	u	┏.

--

Demilitarization:

No

Fiig:

A542a0