Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-108-5980

Cross Sectional Shape:
Round
Thread Class:
3b 1st end

# Thread Direction:

Right-hand 1st end

# Inside Diameter:

0.391 inches

#### **Tempurature Rating:**

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.600 inches

Minimum Inside Bending Radius:

2.875 inches

#### Connection Style:

Swivel nut, flareless 1st end

#### End Connection Design:

Straight 1st end

## **Connection Type:**

Threaded internal tube 1st end

# Features Provided:

Electrostatic discharge capability and reusable end fittings

#### **Burst Test Pressure:**

14000.0 pounds per square inch

#### Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

#### Maximum Operating Pressure:

3000.0 pounds per square inch

## Thread Size:

0.750 inches 1st end

#### Seat Angle:

12.0 degrees 1st end

#### Hydrostatic Test Pressure:

6000.0 pounds per square inch

### **Outer Covering Environmental Protection:**

Corrosion resistant and ethylene glycol resistant and fuel resistant and oil resistant and heat resistant and vibration resistant and

weatherproof

## Inside Surface Condition:

Smooth

#### **Measuring Method And Length:**

51.875 inches working

### **Thread Series Designator:**

Unjf 1st end

Nonmetallic Hose Assembly - Page 2 of 2



# **Specification Data:**

81343-as115 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

Fiig:

A542a0