

View Online at <https://aerobasegroup.com/nsn/4720-00-108-5989>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-60.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.750 inches

Minimum Inside Bending Radius:

3.750 inches

Exterior Color:

Black

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

900.0 pounds per square inch

Layer Composition And Location:

2nd layer braided cotton cord and outer layer molded rubber, synthetic and 1st layer braided cotton cord

Maximum Operating Pressure:

225.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

450.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

72.000 inches

Special Features:

Furnished w/adapter pipe to tube

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unef 1st end

Specification Data:

81349-mil-h-3992 government specification

Specification Or Standard:

1 type and 1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0

Mil-std (military Standard):

Mil-h-3992 spec.