

View Online at <https://aerobasegroup.com/nsn/4720-00-110-3662>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 225.0 degrees fahrenheit single response

**Outside Diameter:**

0.422 inches

**Minimum Inside Bending Radius:**

2.250 inches

**Exterior Color:**

Black

**Hose Or Tubing Specification/std Data:**

Sae j30, 30r3-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 2nd end

**End Fitting Component And Material:**

Complete fitting copper alloy all ends

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Thready Qty Per Inch (tpi):**

27 2nd end

**Second End Relationship With First End:**

Not identical

**Burst Test Pressure:**

1000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

1st layer braided textile yarn

**Maximum Operating Pressure:**

250.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Cold resistant and fuel resistant and oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

42.000 inches

**Second End Swivel Action Capability:**

Not included

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Uns 2nd end

**Specification Data:**

Sae j30, 30r3-81343 national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0