

View Online at <https://aerobasegroup.com/nsn/4720-00-111-2427>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.750 inches

Minimum Inside Bending Radius:

1.750 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Sae j1402, type b-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Nut steel 1st end

Fitting Component And Surface Treatment:

Nut cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

900.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

2nd layer braided fiber

Maximum Operating Pressure:

225.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

450.0 pounds per square inch

Outer Covering Environmental Protection:

Cold resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

23.250 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, chloroprene; furnished with adapter straight @pipe to tube

Thread Series Designator:

Unef 1st end

Specification Data:

Sae j1402, type b-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0